

# PMP



## Gopher-EV

Prairie Machine & Parts | A World Leader in Supplying Underground Mining Equipment

# Rugged, Agile, & 100% Electric

Easy to Adopt electric drive technology

The GOHPER-EV® is a robust electric 2-wheel or 4-wheel drive truck, built for demanding above and underground applications



Open Air Regular Cab Configuration Shown

## Standard Features

- "Mine Duty Ready" to operate in the demanding mining environments
- 2-Wheel or 4-Wheel Drive
- 4-Wheel Independent Suspension
- Adjustable ride height
- Power Rack and Pinion Steering
- Dual Circuit Hydraulic Disc Brakes
- J1772 Charging, 6.6kW or 12.2kW
- Regular & Crew Cab Configuration

## Safe and Dependable

- CLEAN Air
- SAFE LiFePo Batteries
- FAIL SAFE Parking Brake
- Back-up Camera\*
- Traction Control
- Bright LED Lighting & rear work lights
- Certified ROPS (Roll Over Protection)
- Certified FOPS (Fall Protection)\*
- QUIET Electric Motors
- ZERO Emissions
- ZERO Fuel Costs

## Service / Maintenance Features

- Patented modular drive system provides low cost operation
- Regenerative braking reduces brake wear and maintenance
- Rapid Charge\* on crew change and lunch breaks for 24/7 operation
- Proven Reduction on maintenance & operation costs (compared to diesel equivalent)
- Vehicle Diagnostics Tools\*
- Manufactured to Quality Assurance Standard ISO 9001:2008

# Zero Emissions. Zero Compromises.

## SPECIFICATIONS

	<b>Gopher-2</b>	<b>Gopher-L</b>	<b>Gopher-4</b>	<b>Gopher-2X</b>	<b>Gopher-LX</b>	<b>Gopher-4X</b>
<b>PRODUCT DIMENSIONS</b>						
Seating Capacity	2	2	4	2	2	4
Wheelbase	82 in (208 cm)	113 in (287 cm)	113 in (287 cm)	82 in (208 cm)	113 in (287 cm)	113 in (287 cm)
Length	114 in (290 cm)	145 in (368 cm)	145 in (368 cm)	114 in (290 cm)	145 in (368 cm)	145 in (368 cm)
Width	60 in (150 cm)	60 in (150 cm)	60 in (150 cm)	60 in (150 cm)	60 in (150 cm)	60 in (150 cm)
Height	70 (178 cm)	70 (178 cm)	70 (178 cm)	70 (178 cm)	70 (178 cm)	70 (178 cm)
Ground Clearance	9 in (23 cm)	9 in (23 cm)	9 in (23 cm)	9 in (23 cm)	9 in (23 cm)	9 in (23 cm)
Weight	2100 lbs (950 kg)	2300 lbs (1050 kg)	2400 lbs (1090 kg)	2400 lbs (1090 kg)	2600 lbs (1180 kg)	2700 lbs (1225 kg)
GVWR	3500 lb (1590 kg)	3500 lb (1590 kg)	3500 lb (1590 kg)	4000 lb (1800 kg)	4000 lb (1800 kg)	4000 lb (1800 kg)
<b>DRIVE</b>						
Drive	2WD	2WD	2WD	4WD	4WD	4WD
Max Speed	35 km/h	35 km/h	35 km/h	45 km/h	45 km/h	45 km/h
Expected Range	140 km (87 miles)	130 km (80 miles)	120 km (75 miles)	120 km (75 miles)	110 km (68 miles)	100 km (62 miles)
Payload (Max)	1400 lbs (635 kg)	1200 lbs (545 kg)	1100 lbs (500 kg)	1600 lbs (725 kg)	1400 lbs (635 kg)	1300 lbs (590 kg)
Power	39 hp	39 hp	39 hp	58 hp	58 hp	58 hp



**For more information contact your PM&P representative at 1.888.933.4812**

**ISO** | **9001:2008**  
CERTIFIED

**PMP**

**Prairie Machine & Parts Mfg.**  
3311 Millar Avenue  
Saskatoon, SK S7K 5Y5 Canada  
888.933.4812  
pmparts.com